

TRUCK
&
BUS
TIRES

xx
p
u
j
a
7
a
o



BESCHREIBUNG

* Informationen zu Tragfähigkeit und Reifendruck bei verschiedenen

Geschwindigkeiten erhalten Sie vom Hersteller.

** Tragfähigkeit bei Standardgeschwindigkeit und Standardbelastung.

• Unser Unternehmen behält sich das Recht vor, alle Angaben in diesem Katalog ohne vorherige Ankündigung zu ändern.

• Dieser Katalog ersetzt alle früheren Kataloge.

• Alle Angaben dienen nur als Referenz; unser Unternehmen übernimmt keine Verantwortung für Druckfehler.

*** Der visuelle Inhalt des Katalogs ist nur repräsentativ.

Um den passenden Reifen für Ihr Fahrzeug zu finden, wenden Sie sich bitte an den Kfz-Service oder einen autorisierten Händler.

TRUCK & BUS TIRES

LONG HAUL



GH 100



GH 105



GH 110 ECOPLANET



DH 100

REGIONAL



GZ 300



DZ 300

TRAILER



LH 100
ECOPLANET



GH 100



GH 110



LZ 300



LZ 305



LZ 310

MIXED SERVICE (ON - OFF)



GC 700



GC 710



GY 800



DC 700 PLUS

TRAILER (ON-OFF)



LCW 710

OFF ROAD



DM 905

URBAN



GU 500



GUW 550



DUW 550



DU 500

COACH



DH COACH



GH COACH



 starmaxx

Drive Your Business Further



 **starmaxx**

GH 100



GH 100 pattern is suitable to use on all axles on buses and at steer or non-powered second axle on trucks. Tread pattern geometry is optimized to deliver steering and grip on wet roads. Exceptional carcass structure provides outstanding braking performance.



TYRE SIZE	LOAD/SPEED INDEX
245/70 R19.5	136/134M
265/70 R19.5	140/138M
285/70 R19.5	146/144L (145/143M)
295/80 R22.5	152/148M
315/80 R22.5	154/150M (156/150L)


EU LABEL
Average values from all sizes of this specific model.

FUEL EFFICIENCY	WET GRIP	NOISE LEVELS

PATTERN PROPERTIES

- Computer designed tire profile and block arrays offer safe and balanced driving.
- Optimised tread design provides resistance against irregular wear by balancing the pressure equally under load.
- Special tread compound and robust structure ensure longevity and economic fuel consumption.
- Excellent carcass structure is suitable for retreading several times.
- Offers excellent grip and short braking distance with numerous sipes and z-shaped circumferential blocks.
- Circumferential grooves discharge water quickly and efficiently.

POSITION / APPLICATION



GH 105


GH 105 is a steer pattern that is designed for trucks. It provides comfort and maneuverability for a balanced drive on asphalt roads. It can also be used on the non-powered second axle on trucks. Wide tread area and multi dimensional sipes improve mileage and enhance traction. Offers outstanding grip on both wet and dry roads.



TYRE SIZE LOAD/SPEED INDEX

11 R22.5 148/145M


12 R22.5 152/148M



PATTERN PROPERTIES

-  ■ Wide shoulder blocks provide lateral balance for a smooth drive.
-  ■ Circumferential grooves drain water quickly and efficiently.
-  ■ Indented sides of the blocks provide safe brake distance even if the tire is worn.
-  ■ Optimized tread design provides resistance against irregular wear by balancing the pressure equally under load.
-  ■ Special tread compound and robust structure ensure longevity and economic fuel consumption.
-  ■ Medium density sipes provide superior handling and decrease braking distance.
-  ■ Excellent carcass structure is suitable for retreading several times.

POSITION / APPLICATION



GH 110 ECOPLANET



GH 110 Ecoplanet is suitable to use on all axles on buses and at steer or non-powered second axle on trucks. Special tread pattern design ensures even wear throughout the tyre's lifespan. Multiple grooves allow fast water discharge and provide exceptional wet handling on asphalt roads. Wide tread area and multi dimensional sipes improve mileage and enhance traction. Offers outstanding grip on both wet and dry roads.



TYRE SIZE







LOAD/SPEED INDEX

285/70 R19.5	146/144L
295/60 R22.5	150/147L
295/80 R22.5	152/148M
315/60 R22.5	154/150L
315/70 R22.5	156/150L (154/150M)
315/80 R22.5	154/150M (156/150L)
385/55 R22.5	160 K
385/65 R22.5	164K


EU LABEL
Average values from all sizes of this specific model.

FUEL EFFICIENCY	WET GRIP	NOISE LEVELS
A	A-B	69-72 dB
B	B	ABc
C	C	
D	D	
E	E	

PATTERN PROPERTIES

-  Optimized tread pattern improves resistance against irregular abrasion by distributing pressure equally under load.
-  Numerous sipes on the ribs enable exceptional grip.
-  Circumferential grooves provide quick and efficient water discharge.
-  Computer designed tire pattern and five circumferential ribs ensure a balanced and comfortable drive.
-  Special tread compound and robust structure enhance efficiency of fuel consumption and improves longevity.
-  Exceptional carcass structure is suitable for retreading.

POSITION / APPLICATION




DH 100



DH 100 is a drive axle pattern designed for busses and trucks. Provides exceptional traction on asphalt roads. Block array decreases wear and increases wet grip. Optimized tread profile provides resistance against irregular wear under heavy loads. Delivers a safe drive and extended mileage in demanding winter conditions. Suitable for retreading.




TYRE SIZE	LOAD/SPEED INDEX
11 R22.5	148/145M
12 R22.5	152/148M
265/70 R19.5	140/138M
285/70 R19.5	146/144L (140/137M)
295/60 R22.5	150/147L
295/80 R22.5 PLUS	152/148M
315/60 R22.5	152/148L
315/70 R22.5	154/150L (152/148M)
315/80 R22.5	154/150M (156/150L)



PATTERN PROPERTIES

- Optimized tread design provides resistance against irregular wear by distributing the pressure equally under load.
- Reinforced interconnected blocks and carefully arranged block array improve driving balance.
- Circumferential and lateral grooves drain water quickly and efficiently.
- Block array structure provides high traction by generating wide tire contact patch on asphalt in any kind of weather conditions.
- Special tread compound and robust structure ensure longevity and enhance fuel efficiency.
- Excellent carcass structure is suitable for retreading.
- Optimized tread depth increases the tire's lifespan.

POSITION / APPLICATION



GZ 300



GZ 300 pattern is designed for light commercial vehicles and suitable to use on all axles. Strong carcass structure provides high retreadability feature. Delivers balanced drive, perfect comfort and high maneuverability on asphalt roads. Provides exceptional wet grip. The unique pattern design enhances mileage performance.



TYRE SIZE

LOAD/SPEED INDEX

8.5	R17.5	121/120L
215/75	R17.5	126/124M
225/75	R17.5	129/127M
235/75	R17.5	132/130M
245/70	R17.5	136/134M
265/70	R17.5	140/138M


EU LABEL
Average values from all sizes of this specific model.

FUELEFFICIENCY	WET GRIP	NOISE LEVELS
A	A-B	70-71 db
B	C	A-B-C
C	D	
D	E	
E		

PATTERN PROPERTIES

- Unique pattern design and optimized block array provides excellent steering performance.
- Horizontal sipes between circumferential blocks increase traction, decrease braking distance and provide outstanding grip on wet roads.
- Z-shaped block structure provides excellent traction and secure braking performance.
- Stone ejectors inside the grooves prevent pebble penetration inside grooves, protecting the tread and carcass.
- Circumferential grooves drain water quickly and efficiently.
- Provides long life and resistance to irregular wear thanks to its special belt construction, optimized footprint and rigid shoulders.
- All steel construction and specifically designed low profile structure meet all highway usage criteria and offer superior comfort.

POSITION / APPLICATION



DZ 300



DZ 300 is drive axle (traction) pattern designed for light commercial trucks and busses. Having 3PMSF and M+S, DZ 300 provides exceptional grip and braking on snowy roads. Delivers high mileage thanks to its special compound.




TYRE SIZE

LOAD/SPEED INDEX

8.5	R17.5	120/121L
215/75	R17.5	126/124M
225/75	R17.5	129/127M
235/75	R17.5	132/130M
245/70	R19.5	136/134M
265/70	R17.5	140/138M
245/70	R19.5	136/134M

EU LABEL

Average values from all sizes of this specific model.



PATTERN PROPERTIES



- The sipes between the blocks offer enhanced traction, shortened brake distance and excellent wet grip.



- Circumferential and lateral grooves ensure quick and effective water discharge.



- All steel construction and specifically designed low profile structure meet all highway usage criteria.



- Interconnected blocks improves longevity.



- Special belt construction and optimized footprint offer long life and provides resistance against irregular wear.





- Provides long life and resistance to irregular wear thanks to its special belt construction, optimized footprint and rigid shoulders.



- Optimized tread depth provides increases the tire's durability and lifespan.

POSITION / APPLICATION



LH 100 ECOPLANET **M+S**

LH 100 ECOPLANET is a free rolling trailer tire specifically designed for fuel efficiency. It provides exceptional wet grip performance. Its strong carcass structure ensures longevity and reduces irregular wear.



TRAILER AXLE



TYRE SIZE	LOAD/SPEED INDEX
215/75 R17.5	135/133J
235/75 R17.5	143/141J (144/144F)
245/70 R17.5	143/141J (146/146F)
245/70 R19.5	141/140J
265/70 R19.5	143/141J
285/70 R19.5	150/148J

EU LABEL
Average values from all sizes of this specific model.

FUELEFFICIENCY	WET GRIP	NOISE LEVELS
A	A-B	69-73 dB
B	B	ABc
C	C	
D	D	
E	E	

PATTERN PROPERTIES



Five circumferential blocks provide excellent cornering stability.



Optimized pattern design and specially developed tread compound decreases fuel consumption.



Z-shaped block structure provides excellent handling on wet road.



Special angled circumferential grooves minimize pebble penetration while allowing quick and efficient water drainage.



Excellent carcass structure is suitable for retreading several times.

POSITION / APPLICATION



GH 100



GH 100 is a free rolling trailer tire. Tread pattern geometry is optimized to deliver steering and grip on wet roads. Exceptional carcass structure provides outstanding braking performance.



TRAILER AXLE




TYRE SIZE LOAD/SPEED INDEX

245/70 R19.5 FRT 141/140J

265/70 R19.5 FRT 143/141J

285/70 R19.5 FRT 150/148J

FRT: Due to the high load capacity, can be used on free rolling trailer axles.



PATTERN PROPERTIES



Computer designed tire profile and block arrays offer safe and balanced driving.



Optimised tread design provides resistance against irregular wear by balancing the pressure equally under load.



Special tread compound and robust structure ensure longevity and economic fuel consumption.



Excellent carcass structure is suitable for retreading several times.




Offers excellent grip and short braking distance with numerous sipes and z-shaped circumferential blocks.



Circumferential grooves discharge water quickly and efficiently.

POSITION / APPLICATION



LZ 300



LZ 300 is a free rolling trailer tire. Its special pattern design enables exceptional wet grip. Optimised tread area provides resistance against irregular wear. Strong carcass structure is resistant to cuts and stone retention. Its special compound promises longevity.



TRAILER AXLE



TYRE SIZE LOAD/SPEED INDEX

385/65 R22.5	164K
385/55 R22.5	160K
435/50 R19.5	160J
445/45 R19.5	164J


EU LABEL
Average values from all sizes of this specific model.

FUELEFFICIENCY	WET GRIP	NOISE LEVELS
A	A	69-72 (dB)
B	B	A Bc
C	C	
D	D	
E	E	

PATTERN PROPERTIES

-  Optimized tread design provides resistance against irregular wear by balancing the pressure equally under load.
-  Lateral sipes provide short braking distance.
-  Circumferential grooves drain water quickly and efficiently.
-  Five circumferential Ribs provide resistance against irregular wear.
-  High-strength carcass with completely steel frame provides long life and Retreadability.

POSITION / APPLICATION



LZ 305



LZ 305 is a free rolling trailer tire. Special tread design provides exceptional grip on wet roads and ensures outstanding mileage performance.



TYRE SIZE	LOAD/SPEED INDEX
215/75 R17.5	135/133J
235/75 R17.5	143/141J (144/144F)
385/65R22.5	164K*

EU LABEL
Average values from all sizes of this specific model.


FUELEFFICIENCY	WET GRIP	NOISE LEVELS
A	A	69-73
B	B	ABC
C	C	
D	D	
E	E	

* For Trailer and Steer Axle Use

PATTERN PROPERTIES

-  Five circumferential ribs provide resistance against irregular wear.
-  Lateral sipes ensure short braking distance.
-  Circumferential grooves drain water quickly and efficiently.
-  Blocked pattern structure provides superior handling on wet and snowy roads.
-  High-strength carcass with completely steel frame provides long life and retreadability.

POSITION / APPLICATION



• Blue optional

LZ 310



The LZ310 is a trailer tire engineered to combine outstanding durability with exceptional fuel efficiency. Its advanced design ensures reliable performance for both regional and long-haul applications.




TRAILER AXLE



TYRE SIZE LOAD/SPEED INDEX

385/65 R22.5 164K



PATTERN PROPERTIES



Circumferential grooves ensure quick and efficient water evacuation.




Innovative tread design and compound deliver low rolling resistance and enhanced durability.



Five tread blocks enhance resistance to irregular wear.

POSITION / APPLICATION



GH 110



GH 110 ECOPLANET is a free rolling trailer tire. Special tread pattern design ensures even wear throughout the tyre's lifespan. Multiple grooves allow fast water discharge and provide exceptional wet handling on asphalt roads. Wide tread area and multi dimensional sipes improve mileage and enhance traction. Offers outstanding grip on both wet and dry roads.



TRAILER AXLE



TYRE SIZE


LOAD/SPEED INDEX

285/70 R19.5 FRT 150/148J

FRT: Due to the high load capacity, can be used on free rolling trailer axles.

EU LABEL

Average values from all sizes of this specific model.



PATTERN PROPERTIES



- Optimized tread pattern improves resistance against irregular abrasion by distributing pressure equally under load.



- Numerous sipes on the ribs enable exceptional grip.



- Circumferential grooves provide quick and efficient water discharge.



- Computer designed tire pattern and five circumferential ribs ensure a balanced and comfortable drive.





- Special tread compound and robust structure enhance efficiency of fuel consumption and improves longevity.



- Exceptional carcass structure is suitable for retreading.

POSITION / APPLICATION



GC 700

M+S

GC 700 is an all position pattern for mixed service (On and Off road) use. Strong carcass structure delivers exceptional resistance to cutting and chipping. Wide footprint enhances handling and stability while improving mileage. Suitable for retreading multiple times.



TYRE SIZE	LOAD/SPEED INDEX
12	R22.5 152/148L
13	R22.5 156/150K
315/80 R22.5	156/150K (154/150L)


EU LABEL
Average values from all sizes of this specific model.

FUELEFFICIENCY	WET GRIP	NOISE LEVELS
A	A	73 db
B	B	A B C
C	C	
D	D	
E	E	

PATTERN PROPERTIES

-  Special pattern design with blocks of different sizes reduces pattern noise.
-  Wide and closed shoulder structure increases lateral balance and enhances damage resistance.
-  Stone rejecters located among blocks minimize pebble penetration inside grooves.
-  Four circumferential grooves drain water, mud and snow quickly and efficiently, improving handling and increasing service life.
-  Special tread compound provides resistance to wears, cuts and breaks.
-  Offers superior handling and braking performance on roads and construction sites with zigzag block structure.
-  Excellent carcass structure is suitable for retreading multiple times.
-  Reinforced interconnected blocks provide a balanced and comfortable drive.

POSITION / APPLICATION



GC 710


M+S

GC 710 is developed to withstand the challenging conditions of construction sites and off-road use, while simultaneously providing perfect highway performance with extended mileage and improved fuel efficiency features.



TYRE SIZE LOAD/SPEED INDEX

12.00 R24 TL	160/157K
12.00 R24 TT	160/157K
315/80R22.5 TL	156/150L



PATTERN PROPERTIES



Strong circumferential ribs provide maximum resistance against cuts and chips.



Wide channels located on the shoulders improve traction on harsh working conditions including muddy roads.



Zigzag block structure ensures perfect grip and safe braking performance.



Stone ejectors located on groove bases avoid pebble penetration and saves the carcass.



Optimized tread profile evenly distributes weight on the footprint to guarantee long service life by avoiding irregular wear.



Special tread compound provides durability for off-road operations and offers comfort and low rolling resistance for highway use.




Three channels with wide angles enhance traction on challenging road by effectively discharging water and mud.



Steel belted carcass is strong enough to be retreaded several times to multiply the tire's service life.

POSITION / APPLICATION



DC 700 Plus



DC 700 Plus is a drive axle pattern suitable for mixed service. Its special tread compound provides resistance to tears. Delivers high mileage and comfort on asphalt roads. The directional tread design offers exceptional traction along with effective soil discharge and drainage.



TYRE SIZE	LOAD/SPEED INDEX
12	R22.5 152/148L
13	R22.5 156/150K
295/80 R22.5	152/148M
315/80 R22.5	156/150K (154/150L)

EU LABEL
Average values from all sizes of this specific model.

FUEL EFFICIENCY	WET GRIP	NOISE LEVELS
A	A	75 db
B	B	ABC
C	C	
D	D	
E	E	

PATTERN PROPERTIES



- Stone ejectors located deep of grooves decrease stone trapping.



- While reinforced interconnected blocks provide a comfortable drive on motorway it also increases block durability in construction site conditions.



- The directional, block-type tread pattern offers excellent grip and traction on wet, muddy and snowy roads in construction sites, while performing balanced performance on asphalt.



- The sipes between circumferential blocks increase traction on snowy and muddy roads, and provide short braking distance



- Block array with different block sizes improves comfort by minimizing noise.



- Optimized groove design enables excellent water/ mud/snow discharge.

POSITION / APPLICATION



GY 800



Closed structure and pattern compound are specifically engineered for construction and mining site conditions to offer long life and ultimate wear and cut resistance. Provides excellent grip and handling on tough or muddy roads.



MIXED SERVICE




TYRE SIZE LOAD/SPEED INDEX

13	R22.5	TL	156/150K
12.00	R24	TL	160/157K
12.00	R24	TT	160/157K
295/80	R22.5	TL	152/148L
315/80	R22.5	TL	156/150K

EU LABEL

Average values from all sizes of this specific model.



PATTERN PROPERTIES



- Optimized tread profile improves resistance against irregular wear by distributing pressure equally under heavy load.



- Wide and closed shoulder structure improve lateral balance and damage resistance.



- Stone ejectors among the blocks avoid pebble penetration inside groves.



- Three circumferential grooves improve handling and traction by effectively discharging water, mud and snow.



- Specially engineered tread compound and wide blocks provide resistance to wears and cuts.



- Zigzag block structure offers outstanding handling and braking performance on roads and construction sites.




- Strong and durable carcass is suitable for retreading multiple times to maximize service life.



- Interconnected blocks provide a balanced drive on road, while increasing durability on site conditions.

POSITION / VERWENDUNG



LCW 710



LCW 710 is a free rolling trailer tire suitable for mixed service (On and Off road) applications. Special compound enhances longevity by providing exceptional resistance against wear and tears.



TRAILER AXLE



TYRE SIZE


LOAD/SPEED INDEX

385/65 R22.5




160K (158L)

EU LABEL

Average values from all sizes of this specific model.



PATTERN PROPERTIES

- 
■ Optimized tread pattern consisting of wide channels and big blocks provides superior handling and longevity on wet or muddy roads.
- 
■ Reinforced interconnected blocks provide a balanced and comfortable drive while enhancing resistance towards tough site conditions.
- 
■ Optimized grooves drain water, mud and snow quickly and effectively.
- 
■ Unique tread design improves resistance against irregular wear by distributing pressure equally under load.
- 
■ Special tread compound provides resistance to wears, cuts and breaks.
- 
■ Strong carcass structure is suitable for retreading multiple times.

POSITION / APPLICATION



DM 905

M+S

DM 905 is an all position pattern that is suitable for off operating service. Robust tread blocks provide exceptional resistance to tears and offer outstanding traction in tough road conditions. Offers excellent self cleaning feature thanks to its special lug design.


TYRE SIZE
LOAD/SPEED INDEX
13 R22.5
156/150K
13 R22.5
158/156K

PATTERN PROPERTIES



- Reinforced block arrays provide steady driving performance at off road conditions.



- Interconnected reinforced blocks enhance driving balance and offer resistance to chunks.



- Open angled grooves drain mud quickly and eject stones effectively.



- Provides high mileage along with steady off the road driving through optimized tread profile, full/empty rate and tread depth.




- Exclusive compound provides endurance against wear-out, cuts, splits and laceration.



- Durable carcass structure allows retreading.

POSITION / APPLICATION



GU 500



GU 500 is an all season bus tire that is suitable for all positions. Robust compound provides exceptional service for inner-city narrow streets and curbs with stop-and-go traffic. Delivers exceptional mileage performance. Offers high retreadability feature thanks to its strong carcass structure.



TYRE SIZE


LOAD/SPEED INDEX

275/70 R22.5 150/145J (152/148E)

275/70 R22.5 150/148J

EU LABEL

Average values from all sizes of this specific model.



PATTERN PROPERTIES

-  Specially developed tread composition and four wide circumferential ribs separated with sipes provide ultimate performance and longevity in inner-city usage.
-  Z-shaped channels and thin sipes provide safety and traction on wet roads.
-  Circumferential grooves drain water quickly and efficiently.
-  Optimized tread width and tread depth ensures longevity and resistance to abrasion.
-  Different size block array reduces tread noise level.
-  Friction indicators located on sidewalls enable controlling the levels of abrasion.
-  Reinforced sidewalls provide resistance against the impacts of friction to pavement while approaching bus stops.
-  Special tread composition offers high traction and safety under low temperatures.

POSITION / APPLICATION



GUW 550



GUW 550 is suitable to be used as all position tire on innercity vehicles. Robust compound provides exceptional service for innercity narrow streets and stop-and-go traffic. Offers high retreadability thanks to its strong carcass structure. 3PMSF and M+S markings on the tire ensure better grip and braking on snow. Wide tread design enhances mileage of the tire.



TYRE SIZE	LOAD/SPEED INDEX
275/70 R22.5	150/145J (152/148E)
275/70 R22.5	150/145J (152/148J)

EU LABEL
Average values from all sizes of this specific model.

FUEL EFFICIENCY	WET GRIP	NOISE LEVELS
A	A	73 db
B	B	ABC
C	C	
D	D	
E	E	

PATTERN PROPERTIES

-  Five circumferential ribs provide safety, balanced driving and lateral resistance.
-  Z-shaped capillary sipes offer ultimate traction on snowy roads and improves safety by reducing brake distance.
-  Ensures effective water, mud and snow discharge thanks to four circumferential grooves.
-  Optimized block array reduces tread noise level.
-  Specially formulated tread composition and deep blocks provide ultimate performance and longevity by increasing resistance against abrasion caused by frequent stops.
-  Friction indicators located on sidewalls enable controlling the levels of abrasion.
-  Reinforced sidewalls provide resistance against the impacts of friction to pavement while approaching bus stops.
-  Special tread composition offers high traction and safety under low temperatures.
-  Optimized tread width and tread depth enhance longevity by improving resistance against abrasion.

POSITION / APPLICATION



DUW 550



DUW 550 is designed for innercity vehicles especially as drive axle of buses. 3PMSF and M+S markings on the tire prove better grip and braking on winter conditions. Wide tread design enhances mileage performance of the tire.



TYRE SIZE

LOAD/SPEED INDEX

275/70 R22.5 150/145J (152/148E)

275/70 R22.5 152/148J

EU LABEL
Average values from all sizes of this specific model.

FUEL EFFICIENCY	WET GRIP	NOISE LEVELS
A	A	74 db
B	B	ABC
C	C	
D	D	
E	E	

PATTERN PROPERTIES

-  Specially formulated tread composition and deep blocks provide ultimate performance and longevity by increasing resistance against abrasion caused by frequent stops.
-  Z-shaped capillary sipes offer ultimate traction on snowy roads and improves safety by reducing brake distance.
-  Optimized tread width and tread depth enhance longevity by improving resistance against abrasion.
-  Unique tread composition offers high traction and safety under low temperatures.
-  Five circumferential ribs provide safety, balanced driving and lateral resistance.
-  Friction indicators located on sidewalls enable controlling the levels of abrasion.
-  Reinforced sidewalls provide resistance against the impacts of friction to pavement while approaching bus stops.
-  Reinforced interconnected blocks offer ultimate inner city performance.

POSITION / APPLICATION




DU 500



It is a drive axle city bus tire developed for use at low temperatures, on dry, wet and snowy surfaces. It can also be used on the front axle depending on the weather and road conditions.



TYRE SIZE LOAD/SPEED INDEX
275/70 R22.5 150/145J (152/148E)



PATTERN PROPERTIES



The specially developed tread compound provides the traction needed in winter conditions, on snowy and wet surfaces, with four wide circumferential ribs divided by a wide groove and then lamellas. It offers short braking distance.



Thin lamellas placed on the pattern with zigzag channels serve as holding elements. Provides traction and safety on snowy and wet surfaces.



It provides effective water/mud/snow discharge with three circumferential grooves. It minimizes the settling of stones in the channels with the stone pushers at the bottom of the grooves.

POSITION / APPLICATION



• In severe winter conditions, the tire can be fitted to the front axle depending on road conditions.



DH COACH



It is a drive axle bus tire developed to provide balanced driving, excellent grip, and safety on asphalt. It offers low rolling resistance for fuel efficiency and long mileage, ensures safety in all seasons, and delivers superior braking and traction on snow.



TYRE SIZE


LOAD/SPEED INDEX

295/80 R22.5

154/150 M

EU LABEL

Average values from all sizes of this specific model.



PATTERN PROPERTIES



Provides balanced and comfortable driving with an optimized tread pattern and specially designed block arrangement. Offers low noise levels.



The blocks, separated by thin sipes, limits the movement of the blocks during traction and ensures even wear. It also offers low rolling resistance.




Provides high traction with high-density sipes placed on the blocks. It offers superior grip and safety in all seasons.



Provides high traction with high-density sipes placed on the blocks. It offers superior grip and safety in all seasons.

POSITION / APPLICATION



GH COACH



It is an all-axle bus tire developed to provide balanced driving, excellent comfort, and safety on asphalt. It offers low rolling resistance for fuel efficiency and long mileage, ensures safety in all-season use, and provides superior braking and traction on snow.



TYRE SIZE


LOAD/SPEED INDEX

295/80 R22.5

154/150 M

EU LABEL

Average values from all sizes of this specific model.



PATTERN PROPERTIES



- The specially developed tread compound provides the traction needed in winter conditions, on snowy and wet surfaces, with four wide circumferential ribs divided by a wide groove and then lamellas. It offers short braking distance.




- Thin lamellas placed on the pattern with zigzag channels serve as holding elements. Provides traction and safety on snowy and wet surfaces.



- It provides effective water/mud/snow discharge with three circumferential grooves. It minimizes the settling of stones in the channels with the stone pushers at the bottom of the grooves.

POSITION / APPLICATION



The logo for Starmaxx, featuring a stylized 'S' icon followed by the word 'starmaxx' in a bold, lowercase, sans-serif font.

Headquarters - Factory

Petlas Tire Industry and Trade
Kindam Mahallesi Ankara - Kayseri Cd.
No: 2/1 Kırşehir / TÜRKİYE
T: +90 386 252 65 50
F: +90 386 252 65 70

Int. Sales & Marketing

Petlas Tire Industry and Trade Ako Kule
Söğütözü Mh. 2178. Cd. No: 6
06530 Ankara / TÜRKİYE
T. +90 312 309 30 30
F: +90 312 309 22 66

Petlas Tire USA

1111 E. Lincolnway STE 205
Cheyenne, WY 82001 USA

www.starmaxx.com

www.starmaxxtire.com

Made in TÜRKİYE